

WHI943E6XGB

gorenje
Life Simplified

Freestanding wall decorative cooker hood



P.A.S. System



Polyurethane filter



TouchFree coating



LedLight

Re-circulating hoods



Noise level

Useful tips

What capacity do you need?

Wall mounted cooker hood

Venting with air extraction or recirculation

Energy class: **B**

Material of housing/chimney: **stainless steel and glass / stainless steel**

Colour of housing/chimney: **stainless steel and black glass / stainless steel**

Lightning efficiency class: **A**

Grease filtering efficiency class: **B**

Fluid dynamic efficiency class: **B**

Maximum extraction rate by extraction operation: **650 m³/h**

Maximum extraction rate by recirculation operation: **488 m³/h**

Venting tube diameter: **15 cm**

Air flow by extraction version, step 1: **245 m³/h**

Air flow by extraction version, step 2: **360 m³/h**

Air flow by extraction version, step 3: **650 m³/h**

Electronic control

Control setting: **Touch control**

Number of speed positions: **3**

TouchFree Inox

Lamp type: **LED**

On/off light switch

Number of lights: **2**

Power of lights: **6 W**

Perimetric suction

Filter material: **Washable aluminium with polyurethane foam**

Coal filter code (optional as separate purchase): **688572**

Recirculation set number: **683035**

Number of motors: **1**

No return airflow flap: **150 mm**

Max. noise level: **68 dB(A)re 1 pW**

Height: **450 mm**

Min. height of the chimney: **650 mm**

Max. height of the chimney: **980 mm**

Annual energy consumption: **66.9 kWh**

Dimensions (W×H×D): **89.5 × 45 × 38 cm**

Dimensions of packed product (W×H×D): **100.5 × 52 × 56.3 cm**

Net weight: **20.6 kg**

Gross weight: **24.7 kg**

Connected load: **266 W**

Nominal current of fuse: **16 amp**

Product code: **679599**

EAN code: **3838782074271**



<https://eg.gorenje.com/en/product/679599>