

WHI623E1XGB

gorenje
Life Simplified

Freestanding wall decorative cooker hood



P.A.S. System



Polyurethane filter



TouchFree coating



LedLight

Re-circulating hoods



Noise level

Useful tips

What capacity do you need?

Wall mounted cooker hood

Venting with air extraction or recirculation

Energy class: **B**

Material of housing/chimney: **stainless steel and glass / stainless steel**

Colour of housing/chimney: **stainless steel and black glass / stainless steel**

Lightning efficiency class: **A**

Grease filtering efficiency class: **B**

Fluid dynamic efficiency class: **C**

Maximum extraction rate by extraction operation: **560 m³/h**

Maximum extraction rate by recirculation operation: **420 m³/h**

Venting tube diameter: **15 cm**

Air flow by extraction version, step 1: **235 m³/h**

Air flow by extraction version, step 2: **360 m³/h**

Air flow by extraction version, step 3: **560 m³/h**

Mechanic control

Control setting: **Button control**

Number of speed positions: **3**

TouchFree Inox

Lamp type: **LED**

On/off light switch

Number of lights: **2**

Power of lights: **6 W**

Perimetric suction

Filter material: **Washable aluminium with polyurethane foam**

Coal filter code (optional as separate purchase): **688572**

Recirculation set number: **683035**

Number of motors: **1**

No return airflow flap: **150 mm**

Max. noise level: **67 dB(A)re 1 pW**

Height: **450 mm**

Min. height of the chimney: **650 mm**

Max. height of the chimney: **980 mm**

Annual energy consumption: **67.1 kWh**

Dimensions (W×H×D): **59.5 × 45 × 38 cm**

Dimensions of packed product (W×H×D): **71 × 51.9 × 56.2 cm**

Net weight: **15.5 kg**

Gross weight: **18.8 kg**

Connected load: **206 W**

Nominal current of fuse: **16 amp**

Product code: **679562**

EAN code: **3838782073809**



<https://eg.gorenje.com/en/product/679562>